

Pagel

5 APPARATUS AND METHOD FOR APPLYING MUD TO DRYWALL TAPE

This invention is in the field of construction methods and in particular methods for applying drywall mud to drywall tape.

10 BACKGROUND

15  
20  
25  
30  
35  
40  
45  
50  
55  
60  
65  
70  
75  
80  
85  
90  
95  
100  
105  
110  
115  
120  
125  
130  
135  
140  
145  
150  
155  
160  
165  
170  
175  
180  
185  
190  
195  
200  
205  
210  
215  
220  
225  
230  
235  
240  
245  
250  
255  
260  
265  
270  
275  
280  
285  
290  
295  
300  
305  
310  
315  
320  
325  
330  
335  
340  
345  
350  
355  
360  
365  
370  
375  
380  
385  
390  
395  
400  
405  
410  
415  
420  
425  
430  
435  
440  
445  
450  
455  
460  
465  
470  
475  
480  
485  
490  
495  
500  
505  
510  
515  
520  
525  
530  
535  
540  
545  
550  
555  
560  
565  
570  
575  
580  
585  
590  
595  
600  
605  
610  
615  
620  
625  
630  
635  
640  
645  
650  
655  
660  
665  
670  
675  
680  
685  
690  
695  
700  
705  
710  
715  
720  
725  
730  
735  
740  
745  
750  
755  
760  
765  
770  
775  
780  
785  
790  
795  
800  
805  
810  
815  
820  
825  
830  
835  
840  
845  
850  
855  
860  
865  
870  
875  
880  
885  
890  
895  
900  
905  
910  
915  
920  
925  
930  
935  
940  
945  
950  
955  
960  
965  
970  
975  
980  
985  
990  
995

Drywall finishing requires that joints and corners be finished by applying drywall mud thereto, allowing the mud to dry, and sanding smooth. Several coats may be required to provide a smooth finish that is satisfactory. The initial coat on a joint comprises a paper or mesh strip, commonly called drywall tape, which is coated with mud and then applied over the joint. Where the job is done by hand, a coat of mud is generally applied to the joint, the tape is pressed into this mud, and another layer of mud is applied over the tape.

Also known are apparatuses for applying mud to drywall tape by drawing the tape through slots on one side or each side of a pail of mud. Such apparatuses are disclosed in United States  
25 Patent Numbers 5,676,793 to Martin et al.; 5,242,495 to Hammond et al.; and 5,498,287 to Barnfield. These demonstrate a relatively simple and effective means of coating drywall tape with mud.

5

If left standing in these prior art containers, paper drywall tape becomes saturated and deteriorates to the point where same can no longer withstand the force required to pull it through the container of mud. Should the drywall procedure be interrupted for a period of time, the tape may break when next the operator pulls on the free end of the tape extending from the bucket. The operator of the Barnfield or Hammond devices must then remove the mud from the container and re-thread fresh tape through the slots in the container. The Martin device does provide a feeder plate and guide for installation in the container for pulling the tape through the mud and container slots.

#### SUMMARY OF THE INVENTION

It is an object of the present invention to provide a simple, economical method and apparatus that allows for use of a slotted container of mud with drywall tape drawn through the slots and the mud, on an intermittent basis, such that the open container top could be sealed, and the drywall tape left threaded through the slots, for extended periods, such as from one day to the next, or longer.

5

It is a further object of the invention to provide an apparatus for conveniently applying drywall mud to drywall tape.

10 The invention accomplishes the object in one aspect by providing a container with access through slots in opposing sidewalls to thread a free end of a roll of drywall tape. A free end of a roll of drywall tape is threaded from an outside of the container through a first slot, then through the container, then through a second slot to the outside of the container. Drywall mud is placed into the container to a level above the drywall tape and the drywall tape is drawn through the slots, thereby coating same with drywall mud. Coated drywall tape is torn off while leaving a free end of drywall tape outside the container available for grasping and pulling more drywall tape.

When the drywall process is interrupted, a strip of material, such as adhesive tape, is attached to at least one surface of 25 the drywall tape between the roll and the first slot. The strip of adhesive tape is substantially longer than the distance across the container and has a tensile strength substantially unaffected by prolonged exposure to drywall mud.

5 The drywall tape with attached adhesive tape is drawn through the first and second slots until a first end of the strip of adhesive tape extends outside the container and a second end of the adhesive tape remains between the roll and the first slot. The open top of the container is sealed and  
10 the apparatus, with tape still threaded through the container may now be left for a prolonged period of time. While the drywall tape in the container will deteriorate, the adhesive tape will not.

15 When it is desired to re-commence the drywall process, the drywall tape and applied adhesive tape is drawn through the slots until the second end of the strip of adhesive tape exits the container through the second slot. The strip of adhesive tape and attached drywall tape is torn off and discarded,  
20 leaving a free end of drywall tape outside the container available for grasping and pulling more drywall tape.

Some drying and solidification of the mud adjacent to the slots can occur. This can result in undesirable granules of  
25 dried mud on the coated drywall tape when the process is restarted. The slots may be plugged or taped over to prevent drying of the mud. Alternatively

5 The method is suitable for small jobs, since mud coated drywall tape is always quickly available, and an apparatus can be stored for relatively lengthy periods.

In a second aspect the invention provides an apparatus for  
10 applying drywall mud to drywall tape, comprising a base, having a flat bottom surface, a roll end and a dispensing end; a container including an open top, sidewalls and a floor, and attached to an upper surface of the base, between the roll end and dispensing end. A first slot is defined by one sidewall facing the roll end, and a second slot is defined by an  
15 opposite sidewall facing the dispensing end of the base. The slots are located in proximity to the container floor. A cover is operative to releasably seal the open top of the container. A roll feeding member extends upwards from the  
20 roll end of the base. Means are provided to releasably and rotatably mount a roll of drywall tape on the roll feeding member, about a substantially horizontal axis, such that a lower extremity of the roll of drywall tape is above the bottom surface of the base.

25

DESCRIPTION OF THE DRAWINGS:

5 While the invention is claimed in the concluding portions  
hereof, preferred embodiments are provided in the accompanying  
detailed description which may be best understood in  
conjunction with the accompanying diagrams where like parts in  
each of the several diagrams are labeled with like numbers,  
10 and where:

Fig. 1 is a side view of an apparatus for applying mud to  
drywall tape;

15 Fig. 2 is a top view of the apparatus of Fig. 1;

Figs. 4 - 4B are side views of the apparatus of Fig.1  
showing the operation thereof;

20 Fig. 5 is a top view of a piece of adhesive tape applied  
to a length of drywall tape;

25 Fig. 6 is a side view of a slot in a container and a  
strip of drywall tape and attached plastic adhesive  
strip;

Fig. 7 is an end view of the slot, a strip of drywall  
tape and attached plastic adhesive strip of Fig. 6.

5

DETAILED DESCRIPTION OF THE ILLUSTRATED EMBODIMENTS:

Figs. 1 and 2 illustrate an apparatus for applying drywall mud  
10 to drywall tape.

The apparatus comprises a base 1, having a flat bottom surface  
2 for resting on a table or floor, a roll end 3 and a  
dispensing end 4. A container 5 is attached to the upper  
15 surface 6 of the base 1, between the roll end 3 and the  
dispensing end 4. The container 5 includes an open top 7,  
sidewalls 8 and a floor 9. A first slot 10 is defined by one  
sidewall 8r facing the roll end 3 of the base 1, and a second  
slot 11 is defined by an opposite sidewall 8d facing the  
20 dispensing end 4 of the base 1. The slots 10, 11 are located  
in proximity to the floor 9 of the container 5. A cover 12 is  
operative to releasably seal the open top 7 of the container  
5.

25 A roll feeding member 13 extends upwards from the roll end 3  
of the base 1. In the illustrated embodiment, the roll  
feeding member 13 and base 2 are integral, with the roll  
feeding member 13 being a bent upwards extension of the base

5 2. A roll of drywall tape 14 is releasably and rotatably mounted on the roll feeding member 13, about a substantially horizontal axis such that a lower extremity 14a of the roll of drywall tape 14 is above the bottom surface 2 of the base 1. The roll 14 may then rotate freely.

10

The slots 10, 11 defined by the sidewalls 8 are substantially horizontal in the illustrated embodiment. This orientation accommodates feeding from the roll of drywall tape 14, however the slots 10, 11 could be oriented vertically or somewhere in between.

15  
20  
25

A gap 16 is defined by the roll feeding member 13 to accommodate the roll of drywall tape 14. The means to releasably and rotatably mount the roll of drywall tape 14 comprises a horizontal rod 15 extending across the top of the gap 16. A shaft 17 is attached at each end of the rod 15 substantially perpendicular to the horizontal rod 15 and parallel to each other. In the illustrated embodiment the shafts 17 and rod 15 are integral, the shafts 17 being simply bent from the rod 15. The illustrated shafts 17 are substantially parallel and are slidably received in apertures 18 defined by the roll feeding member 13 on each side of the gap 16. The rod 15 may thus be readily removed



5 from the apparatus for removing or replacing the roll of  
drywall tape 14.

The illustrated apparatus can be used to practice the method  
of the invention for applying drywall mud to drywall tape  
10 allowing for lengthy stoppages in a drywall application  
process.

05002746T = 050T50T  
15 A free end 20 of a roll of drywall tape 14 is threaded from  
outside the container 5 through the first slot 10, then  
through the container 5, then through the second slot 11 to  
the outside of the container 5. Drywall mud 21 is placed into  
the container 5 to a level above the drywall tape 22. The  
drywall tape 22 is drawn through the slots 10, 11 thereby  
coating same with drywall mud 21. The coated drywall tape 22c  
is torn off as needed while always leaving a free end 20 of  
drywall tape 22 outside the container 5 available for grasping  
and pulling more drywall tape 22.

25 When the drywall process is interrupted, such as when the work  
day is finished, none of the prior art allows the drywall tape  
22 to be left in mud 21, as the paper drywall tape will very  
quickly deteriorate by absorbing moisture from the mud 21 such  
that when it is attempted to grasp the free end 20 of the

5 drywall tape 22 and pull more through the container 5, the drywall tape 22 will break. The operator must then remove mud 21 from the container 5 and re-thread drywall tape 22 through the container 5.

10 To avoid this there is attached to the drywall tape 22, between the roll 14 and the first slot 10, a strip of material having a tensile strength substantially unaffected by prolonged exposure to drywall mud 21. The strip of material is substantially longer than the distance across the container  
15 5 between the first and second slots 10, 11. The strip may be attached to the drywall tape 22 by adhesives, staples or similar means.

20 The strip of material may be plastic film 23 such as is illustrated in Fig. 3, whose tensile strength is unaffected by exposure to mud 21 and is also impervious to moisture from mud 21. The plastic film 23 is attached to the drywall tape 22 by simply wrapping same around the drywall tape 22 so as to surround a portion of drywall tape 22 and prevent moisture  
25 from the mud 21 contacting the portion of drywall tape 22. The seam 23s may be sealed with glue or tape. This method prevents deterioration of the drywall tape 22 and allows same to remain in the mud 21 for prolonged periods and pulled

10

15

**U20**

Alternatively, as illustrated in Figs. 6 and 7, the slots 10, 11 may be sealed by providing a strip of material, such as

25

In Figs. 4, 4A and 4B, a second strip of adhesive tape 25a is adhesively attached to the drywall tape 22 on a side thereof opposite the strip of adhesive tape 25, however in most

5 situations a strip of adhesive tape 25 on one side of the  
drywall tape 22 should suffice, provided the portion extending  
between the roll 14 and first slot 10 is adhered strongly  
enough to pull the drywall tape through the container 5. As  
illustrated in Fig. 5, for maximum strength of adhesion, the  
10 adhesive tape 25 has a width substantially equal to a width of  
the drywall tape 22.

The foregoing is considered as illustrative only of the  
principles of the invention. Further, since numerous changes  
15 and modifications will readily occur to those skilled in the  
art, it is not desired to limit the invention to the exact  
construction and operation shown and described, and  
accordingly, all such suitable changes or modifications in  
structure or operation which may be resorted to are intended  
20 to fall within the scope of the claimed invention.